

















接続機器機種一覧表

【凡例】 ○：有り ×：無し -：該当無し

分類	基本形式	定格通電電流	定格絶縁電圧	端子ねじサイズ		最大適合 接続電線	適合圧着端子	連結タイプ				極数固定タイプ		掲載ページ
				クイックアップねじ	レール搭載			金具固定式		固定タイプ 有無	極数			
					レール式 有無			最大連結数 (1mレール)	固定式 有無			最大連結数		
制御 / 主回路用端子台	SA形 	20A	600V	M4x8 なべ小ねじ	×	5.5mm ²		×	-	×	-	○	2,3,4,6,8, 10,12,16	D-7
	RB形 ※ウィスカ対策品も 製作可能です。 	30A	600V	M4x8 なべ小ねじ	○	5.5mm ²		○	85P	×	-	×	-	D-15
	MB形 	30A	600V	M5x10 なべ小ねじ	×	8mm ²		×	-	×	-	○	2,3,4,6,8, 10,12	D-11
	HC形 	70A	660V	M5x10 六角ボルト	×	14mm ²		○	55P	○	15P	×	-	D-23
		90A 		M6x12 六角ボルト	×	22mm ²		○	45P	○	15P	×	-	
		130A 		M8x18 六角ボルト	×	38mm ²		○	30P	○	12P	×	-	
		175A 		M8x18 六角ボルト	×	60mm ²		○	25P	○	12P	×	-	
		300A 		M10x25 六角ボルト	×	150mm ²		○	15P	○	9P	×	-	
		400A 		M12x25 六角ボルト	×	250mm ²		○	15P	○	9P	×	-	
		600A 		M16x35 六角ボルト	×	325mm ²		○	15P	○	6P	×	-	

[凡例] ○：有り ×：無し -：該当無し

分類	基本形式	定格通電電流	定格絶縁電圧	端子ねじサイズ		最大適合 接続電線	適合圧着端子	連結タイプ				極数 固定タイプ		掲載 ページ
				クイックアップねじ	ルール搭載			金具固定式		配列 有無	極数			
					ルール式 有無			最大連結数 (1mルール)	固定式 有無			最大連結数		
特殊 端子 台	AT形コンデンサ端子台 *ウイスカ対策品 	30A	600V	M4x8 なべ小ねじ	○	5.5mm ²		○	86P	×	-	×	-	D-39
	60A	M5x10 なべ小ねじ		○	14mm ² (アース端子 5.5mm ²)		○	68P	×	-	×	-		
	DC形断路器端子台 	20A	660V	M4x8 なべ小ねじ	○	5.5mm ²		○	85P	○	30P	×	-	D-59
	TD形コネクタ端子台 	15A	600V	M3.5x7 なべ小ねじ	×	2.0mm ²		○	9P	×	-	○	10	D-81
テ ス ト 端 子	SH形テスト端子 	20A	250V	M4x10 なべ小ねじ	×	5.5mm ²		×	-	×	-	○	1	D-75
コ ネ ク タ	PCA形コネクタ 	15A	600V	M4x8 なべ小ねじ	×	5.5mm ²		×	-	×	-	○	12P および 20P	D-89